## Description

Heterogeneous indoor floorcovering, 9.4mm thick.

## 1: SUPERIOR PERFORMANCE AND LONGTERM SAVINGS

Omnisports is backed with a single surface embossing combined with TopClean XP ™

2: EXTREME PROTECTION AND DURABILITY

## Vinyl wear layer 3: DYNAMIC COLOURS AND REALISTIC DECORS

High definition printing for a realistic wood surface appearance and built-in unis for

4: OUTSTANDING DIMENSIONAL STABILITY < 0.10%:

Extremely tough single glass veil reinforcement 5: HIGH PERFORMANCE AND DURABILITY:

Homogeneous calendared sheet made from up to 60% recycled vinyl.

6: COMFORT, SAFETY AND BOOSTED SPORTS EXPERIENCE:

High-density closed-cell foam with engineered honeycomb backing.



PROPERTIES	STANDARDS	OMNISPORTS PUREPLAY
DECLARATION OF PERFO	ORMANCE	
	0120-071-DoP-2016-04	
CLASSIFICATION		
ype of floor covering	EN 14904	Heterogeneous indoor floorcoverings
TECHNICAL CHARACTER	RISTICS	
otal thickness	ISO 24346 (EN 428)	9.4mm
otal weight	ISO 23997 (EN 430)	6200g/m²
Vidth	ISO 24341 (EN 426)	2m
ength	ISO 24341 (EN 426)	20.5lm
REQUIREMENTS FOR SA	FE USE	
riction	EN 13036-4	80 to 110
shock absorption	EN 14808	P2
		≥35%
ertical deformation	EN 14809	P2
pecular gloss	EN ISO 2813	≤30
TECHNICAL PERFOMAN	CES	
ertical ball behaviour	EN 12235	≥90%
Reaction to fire	EN 13501-1	Cfl-s1*
esistance to wear	EN ISO 5470-1	≤1g
Resistance to indentation	Average measured value	Compliant
	EN 1516	≤0.50mm
esistance to a rolling load	EN 1569	≤0.50mm
coustic efficiency	EN ISO 717-2	21dB
hermal resistance	EN ISO 14456	Approx. 0.14 m² K/W
		Compatible with underfloor heating

























Installation and maintenance guides available on Tarkett Sports Indoor website

Technical data in force as from the date of publication (08/2022).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett Sports.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.



<sup>\*</sup> glued and GreenLay installation on concrete